

HOT WATER STATIONARY - PAINTED

Largo Hot Water Stationary Systems are the preferred choice in a Cleaning System. These Units last for years and provide dependable proven service in trucking, farming, heavy equipment shops and maintenance facilities. These units can be equipped with numerous options like Remote Cleaning Stations, Clutch Driven Pumps, Soap Solenoids, Steam Combo, Multi-Gun Units, Variable Pressure Wand and Foam Lances.

STANDARD FEATURES:

- Belt Driven General Plunger Pump
- 50' 3/8" Quick Coupled Hose
- Industrial Strength Baldor Electric Motor
- Sch 80 Black Pipe Heating Coil
- High Pressure Detergent
- Black Powder Coated Industrial Grade Frame
- PAC Inline Thermostats
- Trigger Gun Control with 4' Lance
- Stainless Steel Coil Wrapper
- NG or LP Fired - Electronic Ignition
- 24 Volt Controls
- Stainless Steel Float Tank & Control Panel
- Honeywell Gas Controls LP/NG
- Quick Coupled Color Coded Spray Tips
- Pressure Relief Valve
- Heavy Duty Unloader Valve
- 35' GFCI on 1PH Units under 30 Amps
- 10' Power Cord on 1PH Units over 30 Amps and on 3PH Units
- Adj. Time Delay Shutdown-Push Button Restart
- ALSO AVAILABLE WITH STAINLESS STEEL FRAME



Specify: Right or Left Coil
Voltage 208-230 or 460 VAC
Natural or LP Gas

MODEL	GPM	PSI	HP	VOLT	Ph	AMPS	SHIPPING WEIGHT	DIMENSIONS
64	4.0	2300	6	208/230	1	25	600	46L x 20W x 44H
64-3	4.0	2000	5	208/230/460	3	17/16/8	600	46L x 20W x 44H
643	4.0	3000	7.5	208/230	1	36	600	46L x 20W x 44H
643-3	4.0	3000	7.5	208/230/460	3	26/25/16	600	46L x 20W x 44H
65	5.0	1800	6	208/230	1	28	720	46L x 20W x 54H
65-3	5.0	1500	5	208/230/460	3	17/16/8	720	46L x 20W x 54H
66	5.0	2000	7.5	208/230	1	36	720	46L x 20W x 54H
66-3	5.0	2000	7.5	208/230/460	3	26/25/15	720	46L x 20W x 54H
67	5.0	3000	10	208/230	1	42	735	46L x 20W x 54H
67-3	5.0	3000	10	208/230/460	3	35/34/15	735	46L x 20W x 54H



LARGO CLEANING SYSTEMS

40 Sevier Lane • Decaturville, TN 38329
Phone: (731) 852-2324 • Fax: (800) 626-7384
www.gcalargo.com • sales@gcalargo.com

DISTRIBUTED BY: